

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.		
09/942,628	08/31/2001	Gary Q. Jin	11775-US	9081		
33361	7590 11/22/2005		EXAM	EXAMINER		
ADAMS PA	ATENT & TRADEMARK	YAO, KW.	YAO, KWANG BIN			
	1100, STATION H ON K2H 7T8		ART UNIT	PAPER NUMBER		
CANADA	O		2667			
			DATE MAILED: 11/22/200:	5		

Please find below and/or attached an Office communication concerning this application or proceeding.

				N 01~		
		Application No.	Applicant(s)	H		
Office Action Summary		09/942,628	JIN, GARY Q.			
		Examiner	Art Unit	· · · · · · · · · · · · · · · · · · ·		
		Kwang B. Yao	2667			
Period fo	The MAILING DATE of this communication app or Reply	pears on the cover sheet w	ith the correspondence addre	ess		
WHIC - Exte after - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DANSIONS of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. O period for reply is specified above, the maximum statutory period were to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing ed patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNIONS (a). In no event, however, may a rivill apply and will expire SIX (6) MON, cause the application to become AB	CATION. reply be timely filed ITHS from the mailing date of this comm BANDONED (35 U.S.C. § 133).			
Status						
1)⊠	Responsive to communication(s) filed on 29 O	<u>ctober 2005</u> .				
2a) <u></u> ☐	This action is FINAL . 2b)⊠ This action is non-final.					
3)	☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
	closed in accordance with the practice under E	Ex parte Quayle, 1935 C.D). 11, 453 O.G. 213.			
Disposit	ion of Claims					
-	Claim(s) 2,3 and 10-40 is/are pending in the ap 4a) Of the above claim(s) is/are withdraw					
	Claim(s) is/are allowed.					
6)⊠	Claim(s) 2,3 and 10-40 is/are rejected.		·			
7)	Claim(s) is/are objected to.					
8)□	Claim(s) are subject to restriction and/or	r election requirement.				
Applicati	ion Papers					
9)[The specification is objected to by the Examine	r.				
10)	The drawing(s) filed on is/are: a) acce	epted or b)□ objected to	by the Examiner.			
	Applicant may not request that any objection to the	drawing(s) be held in abeyar	nce. See 37 CFR 1.85(a).			
	Replacement drawing sheet(s) including the correct	· -		• •		
11)	The oath or declaration is objected to by the Ex	aminer. Note the attached	d Office Action or form PTO-	152.		
Priority ι	ınder 35 U.S.C. § 119					
· ·	Acknowledgment is made of a claim for foreign ☐ All b) ☐ Some * c) ☐ None of:	priority under 35 U.S.C. §	§ 119(a)-(d) or (f).			
	1. Certified copies of the priority documents	s have been received.				
	2. Certified copies of the priority documents		·· —			
	3. Copies of the certified copies of the prior	•	received in this National Sta	age		
* 0	application from the International Bureau		rospiyad			
	See the attached detailed Office action for a list	or the certified copies not	receivea.			
Attachmen	• •	_		·		
	e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (PTO-948)		Summary (PTO-413) s)/Mail Date			
3) 🔲 Infor	nation Disclosure Statement(s) (PTO-1449 or PTO/SB/08) r No(s)/Mail Date	_	nformal Patent Application (PTO-15	2)		

Art Unit: 2667

DETAILED ACTION

Response to Amendment

1. Applicant's request for reconsideration of the finality of the rejection of the last Office action is persuasive and, therefore, the finality of that action is withdrawn.

Claim Objections

2. Claims 19 and 24 are objected to because of the following informalities: claims 19 and 24 depend on the canceled claims 4 and 9, respectively. Appropriate correction is required.

Claim Rejections - 35 USC § 112

3. Claims 3, 18 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 3, line 3, it is not clear what is meant by "implementation of the and up-sampling means".

Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an

Art Unit: 2667

international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 11, 15, 17, 20, 25, 30, 31, 36 are rejected under 35 U.S.C. 102(e) as being 5. anticipated by Wallace et al. (US 6,473,467).

Wallace et al. disclose a communication system comprising the following features: Regarding claim 11 wherein said FFT (FIG. 6, FFT 614A, 614R) is implemented for only a single side band of said sub-bands (column 11, lines 41-57; column 19, lines 47-57); regarding claim 15, when the method is used in a frequency division multiplexing application, the bandwidth varies from one subband to another (column 19, line 58 to column 20, line 9), with a corresponding variation of size of said plurality of different FFTs (FIG. 6, FFT 614A, 614R); regarding claim 17, a broad bandwidth, high data rate communications system employing Fast Fourier Transform comprising a transmitter (FIG. 3, TRANSMITTER 100) and a receiver (FIG. 6, RECEIVER), the transmitter (FIG. 3, TRANSMITTER 100) having means for dividing the bandwidth into sub-bands (column 11, lines 41-57; column 19, lines 47-57) each for a corresponding sub-band signal; and means for performing Inverse Fast Fourier Transform IFFT (FIG. 3, IFFT 320A, 320B, 320T) upon the sub-band signals using, for each sub-band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) and transmitting the transformed signals to the receiver (FIG. 6, RECEIVER); the receiver (FIG. 6, RECEIVER) having means for receiving the transformed sub-band signals and performing forward Fast Fourier Transform thereupon using, for each transformed sub-band signal, a respective ogle of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) corresponding to those in the transmitter (FIG. 3, TRANSMITTER 100); regarding claim 20, a transmitter (FIG. 3, TRANSMITTER 100) for use in a broad bandwidth, high data rate communications system employing Fast Fourier

Art Unit: 2667

Transform, the transmitter (FIG. 3, TRANSMITTER 100) having means for dividing the bandwidth into sub-bands (column 11, lines 41-57; column 19, lines 47-57) each for a corresponding sub-band signal; and means for performing Inverse Fast Fourier Transform IFFT (FIG. 3, IFFT 320A, 320B, 320T) upon the sub-band signals using, for each sub-band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R); regarding claim 25, A receiver (FIG. 6, RECEIVER) for use in a broad bandwidth, high data rate communications system employing Fast Fourier Transform FFT (FIG. 6, FFT 614A, 614R), in which transmitted signals are divided into sub bands and converted using, for each sub band signal, a respective one of a plurality of Inverse Fast Fourier Transforms IFFTs (FIG. 3, IFFT 320A, 320B, 320T), the receiver (FIG. 6, RECEIVER) having: means for receiving a plurality of subband signals in said corresponding plurality of sub bands; and means for performing Fast Fourier Transform upon the received sub band signals using, for each sub band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) corresponding to the IFFTs (FIG. 3, IFFT 320A, 320B, 320T); regarding claim 30, a method of implementing a Fast Fourier Transform FFT (FIG. 6, FFT 614A, 614R) in a broad bandwidth, high data rate communications system comprising a transmitter (FIG. 3, TRANSMITTER 100) and a receiver (FIG. 6, RECEIVER), the method comprising the steps of at the transmitter (FIG. 3, TRANSMITTER 100), dividing the bandwidth into sub bands each for a corresponding sub band signal; and performing Inverse Fast Fourier Transform IFFT (FIG. 3, IFFT 320A, 320B, 320T) upon the sub band signals using, for each subband signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) and transmitting the transformed subband signals to the receiver (FIG. 6, RECEIVER); and at the receiver (FIG. 6, RECEIVER), performing forward Fast Fourier Transform upon the received

Application/Control Number: 09/942,628 Page 5

Art Unit: 2667

transformed sub band signals using, for each sub band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) corresponding to those in the transmitter (FIG. 3, TRANSMITTER 100); regarding claim 31, A method of processing signals for transmission by a transmitter (FIG. 3, TRANSMITTER 100) in a broad bandwidth, high data rate communications system employing Fast Fourier Transform, the method comprising the steps of dividing the bandwidth into sub bands each for a corresponding sub band signal; and performing Inverse Fast Fourier Transform IFFT (FIG. 3, IFFT 320A, 320B, 320T) upon the sub band signals using, for each sub band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R); regarding claim 36, A method of processing received signals in a receiver (FIG. 6, RECEIVER) in a broad bandwidth, high data rate communications system employing Fast Fourier Transform FFT (FIG. 6, FFT 614A, 614R), in which transmitted signals are divided into sub bands and converted using, for each sub band signal, a respective one of a plurality of Inverse Fast Fourier Transforms IFFTs (FIG. 3, IFFT 320A, 320B, 320T), the receiving method comprising the steps of receiving a plurality of said sub band signals in a corresponding plurality of sub bands; and performing Fast Fourier Transform upon the received sub band signals using, for each sub band signal, a respective one of a plurality of different FFTs (FIG. 6, FFT 614A, 614R) corresponding to the IFFTs (FIG. 3, IFFT 320A, 320B, 320T). See column 1-29.

Claim Rejections - 35 USC § 103

- 6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person

Art Unit: 2667

having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

7. Claims 2, 3, 10, 12, 13, 14, 16, 21, 22, 26, 27, 32, 33, 37, 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wallace et al. (US 6,473,467) in view of Murakami (US 6,317,409).

Wallace et al. disclose the claimed limitations above. Wallace et al. further discloses the following features: regarding claim 13, the step of using a modulator (Fig. 3, modulator 114A, 114B, 114T) to process each sub-band separately prior to implementation of the FFT (FIG 6, FFT 614A, 614R). Wallace et al. does not disclose the following features: regarding claim 2, wherein the transmitter and receiver each further include pass band filters to isolate desired sub-band frequencies; regarding claim 3, wherein the transmitter has a modulator to process each sub-band separately prior to implementation of the and up-sampling means in advance of the filter to up-sample each sub-band signal to the desired sampling rate, the receiver having corresponding down-sampling means and a corresponding demodulator; regarding claim 10, at each of the transmitter and the receiver, the step of providing using pass band filters to isolate desired sub-band frequencies; regarding claim 12, wherein a single side band filter is used; regarding claim 14, wherein before said filtering, each sub-band signal is un-sampled to the desired sampling rate; regarding claim 16, wherein up and down sampling rates also vary correspondingly; regarding claim 21, including pass band filters to isolate desired sub band frequencies; regarding claim 22, having a modulator to process each sub band separately prior to implementation of the IFFT and up sampling means in advance of the pass band filters to up sample each sub band signal to the desired sampling rate; regarding claim 26, wherein the receiver further includes pass band filters to isolate desired sub band frequencies; regarding

Art Unit: 2667

claim 27, for use with received sub band signals that have been modulated separately prior to implementation of the IFFT and up sampled, the receiver having corresponding down sampling means and a corresponding demodulator; regarding claim 32, wherein pass band filters are used to isolate desired sub band frequencies; regarding claim 33, wherein a modulator is used to process each sub band separately prior to implementation of the IFFT and each sub band signal is up sampled to the desired sampling rate prior to passband filtering; regarding claim 37, wherein the receiver a received signal is filtered using pass band filters to isolate desired sub band frequencies; regarding claim 38, for processing received sub band signals that have been modulated separately prior to implementation of the IFFT and up sampled, the method comprising the steps of down sampling and demodulating the received sub band signals using a complementary demodulator and down sampling rate.

Murakami discloses a communication system comprising the following features:

Regarding claim 2, wherein the transmitter and receiver each further include pass band filters

(FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to isolate desired sub-band frequencies; regarding claim 3, wherein the transmitter has a modulator (FIG 1, Modulator 3) to process each sub-band separately prior to implementation of the and up-sampling (FIG. 2, up-sampler 130) means in advance of the filter (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to up-sample (FIG. 2, up-sampler 130) each sub-band signal to the desired sampling rate, the receiver having corresponding down-sampling (FIG. 10, down sampler ↓M) means and a corresponding demodulator (FIG 1, demodulator 5); regarding claim 10, at each of the transmitter and the receiver, the step of providing using pass band filters (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to isolate desired sub-band

Art Unit: 2667

frequencies; regarding claim 12, wherein a single side band filter (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) is used; regarding claim 14, wherein before said filtering (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43), each sub-band signal is un-sampled to the desired sampling rate; regarding claim 16, wherein up (FIG. 2, up sampler 130 \uparrow K) and down-sampling (FIG. 10, down sampler \downarrow M) rates also vary correspondingly; regarding claim 21, including pass band filters (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to isolate desired sub band frequencies; regarding claim 22, having a modulator (FIG 1, Modulator 3) to process each sub band separately prior to implementation of the IFFT (FIG. 2, M-point IFFT 120) and up sampling means in advance of the pass band filters (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to up-sample (FIG. 2, up-sampler 130) each sub band signal to the desired sampling rate; regarding claim 26, wherein the receiver further includes pass band filters (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to isolate desired sub band frequencies; regarding claim 27, for use with received sub band signals that have been modulated separately prior to implementation of the IFFT (FIG. 2, M-point IFFT 120) and up-sample (FIG. 2, up-sampler 130) d, the receiver having corresponding down-sampling (FIG. 10, down sampler \downarrow M) means and a corresponding demodulator (FIG 1, demodulator 5); regarding claim 32, wherein pass band filters (FIG. 1, O0(z), O1(z); column 4. lines 20-22; column 5, lines 28-43) are used to isolate desired sub band frequencies; regarding claim 33, wherein a modulator (FIG 1, Modulator 3) is used to process each sub band separately prior to implementation of the IFFT (FIG. 2, M-point IFFT 120) and each sub band signal is upsample (FIG. 2, up-sampler 130) d to the desired sampling rate prior to passband filtering (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43); regarding claim 37, wherein the

Art Unit: 2667

receiver a received signal is filter (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43)ed using pass band filters (FIG. 1, Q0(z), Q1(z); column 4, lines 20-22; column 5, lines 28-43) to isolate desired sub band frequencies; regarding claim 38, for processing received sub band signals that have been modulated separately prior to implementation of the IFFT (FIG. 2, M-point IFFT 120) and up-sample (FIG. 2, up-sampler 130) d, the method comprising the steps of down-sampling (FIG. 10, down sampler \downarrow M) and demodulating (FIG 1, Modulator 3) (FIG 1, demodulator 5) the received sub band signals using a complementary demodulator (FIG 1, demodulator 5) and down-sampling (FIG. 10, down sampler \downarrow M) rate. See column 1-14. It would have been obvious to one of the ordinary skill in the art at the time of the invention to modify the system Wallace et al., by using the features, as taught by Murakami, in order to provide an efficient data communication without inducing inter-channel interference. See Murakami, column 2, lines 28-34.

8. Claims 18, 19, 23, 24, 28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wallace et al. (US 6,473,467) in view of Murakami (US 6,317,409) as applied to claims 17, 2, 3, 20-22, 25-27 above, and further in view of Kim et al. (US 6,690,717).

Wallace et al. and Murakami disclose the claimed limitations above. Wallace et al. and Murakami do not disclose the following features: regarding claim 18, wherein the transmitter and receiver are configured for transmitting and receiving, respectively, Discrete Multi tone DMT signals via a Digital Subscriber Line DSL; regarding claim 19, wherein the transmitter and receiver arc conflgured for use with a Very high rate Digital Subscriber Line VDSL; regarding claim 23, configured for transmitting Discrete Multi tone DMT signals via a Digital Subscriber Line DSL; regarding claim 24, configured for use with a Very high rate Digital Subscriber Line

Art Unit: 2667

VDSL; regarding claim 28, configured for receiving said sub-band signals in the form of Discrete Multi-tone DMT signals via a Digital Subscriber Line DSL.

Kim et al. discloses a communication system comprising the following features: regarding claim 18, wherein the transmitter and receiver are configured for transmitting and receiving, respectively, Discrete Multi tone DMT signals via a Digital Subscriber Line DSL (column 2, lines 56-67); regarding claim 19, wherein the transmitter and receiver arc confl gured for use with a Very high rate Digital Subscriber Line VDSL (column 2, lines 56-67); regarding claim 23, configured for transmitting Discrete Multi tone DMT signals via a Digital Subscriber Line DSL (column 2, lines 56-67); regarding claim 24, configured for use with a Very high rate Digital Subscriber Line VDSL (column 2, lines 56-67); regarding claim 28, configured for receiving said sub-band signals in the form of Discrete Multi-tone DMT signals via a Digital Subscriber Line DSL (column 2, lines 56-67). It would have been obvious to one of the ordinary skill in the art at the time of the invention to modify the system Wallace et al. and Murakami, by using the features, as taught by Kim et al., in order to provide a broader bandwidth and transmit with better quality of data. See Kim et al., column 2, lines 46-51.

9. Claims 29, 34, 35, 39, 40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wallace et al. (US 6,473,467) in view of Kim et al. (US 6,690,717).

Wallace et al. discloses the claimed limitations above. Wallace et al. does not disclose the following features: regarding claim 29, configured for use with a Very high rate Digital Subscriber Line VDSL; regarding claim 34, the step of transmitting the transformed sub bands signals as Discrete Multi tone DMT signals via a Digital Subscriber Line DSL; regarding claim 35, wherein the transformed sub band signals are transmitted via a Very high rate Digital

Art Unit: 2667

Subscriber Line VDSL; regarding claim 39, wherein said sub band signals are received in the form of Discrete Multi tone DMT signals via a Digital Subscriber Line DSL; regarding claim 40, wherein said sub band signals are received via a Very high rate Digital Subscriber Line VDSL.

Kim et al. discloses a communication system comprising the following features: regarding claim 29, configured for use with a Very high rate Digital Subscriber Line VDSL (column 2, lines 56-67); regarding claim 34, the step of transmitting the transformed sub bands signals as Discrete Multi tone DMT signals via a Digital Subscriber Line DSL (column 2, lines 56-67); regarding claim 35, wherein the transformed sub band signals are transmitted via a Very high rate Digital Subscriber Line VDSL (column 2, lines 56-67); regarding claim 39, wherein said sub band signals are received in the form of Discrete Multi tone DMT signals via a Digital Subscriber Line DSL (column 2, lines 56-67); regarding claim 40, wherein said sub band signals are received via a Very high rate Digital Subscriber Line VDSL (column 2, lines 56-67). It would have been obvious to one of the ordinary skill in the art at the time of the invention to modify the system Wallace et al., by using the features, as taught by Kim et al., in order to provide a broader bandwidth and transmit with better quality of data. See Kim et al., column 2, lines 46-51.

Conclusion

10. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kwang B. Yao whose telephone number is 571-272-3182. The examiner can normally be reached on M-F.

Art Unit: 2667

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Chi H. Pham can be reached on 571-272-3179. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

KWANG BIN YAO PRIMARY EXAMINER

November 15, 2005